

## PTSPower, LLC – PTS Industrial – See Quote/Contact

### REBUILDING PRODUCTS:

#### Duro-Wear

DUROMAR DURO-WEAR is a specially formulated 100% solids epoxy lining used for the protection and repair of areas subjected to severe abrasion and impact. Areas coated with DURO-WEAR are tough, abrasion and chemically resistant to a wide range of environments.

---

#### EXP-Thixset

DUROMAR EXP-THIXSET is a more chemical and higher temperature resistant version of either SAR or HAR used primarily in areas operating at higher temperatures and requiring better chemical resistance. Applications include acid tank repair, boiler skirts or refinery evaporator vessels.

---

#### HAR

DUROMAR HAR is more abrasion resistant putty than SAR, which is used primarily in areas requiring more resistance to fine slurries either in liquid or powder form. Common applications are in coal mills, chutes, ash hoppers or deflector plates in FGD systems.

---

#### MG-F

DUROMAR MG-F is stainless steel filled putty, which is engineered for use where final precision machining is required. Typical applications include shaft repairs, pump parts, bearing housings, or anywhere requiring final machining to close tolerances.

---

#### SAR

DUROMAR SAR is versatile easy-to-use rebuilding putty with excellent abrasion and chemical resistance. This product is heavily filled with aluminum oxide and can be built up to an inch in thickness or more. Typical applications are for rebuilding of pump casings, slurry tanks, weld seams or anywhere requiring the restoration of metal components.

---

#### Ultra-Build

DUROMAR ULTRA-BUILD is a rugged, durable, trowel grade product filled with ceramic beads and other abrasion resistant fillers. It is used primarily in areas where abrasion resistances to both small and coarse slurries are required over large areas. It is typically used in the mining industry on chutes, hoppers, classifiers or mills. It can be built up to 2" in thickness or more in a single coat.